ISS360

HIGH PERFORMANCE IMAGING SONAR

SUBSEA INNOVATIVE SENSORS

FEATURES & BENEFITS

> 90 METER RANGE

Long range imaging.

6,000 & 4,000M DEPTH RATINGS

Ideal for Shallow and Deep Waters.

> PITCH & ROLL*

Provides Pitch and Roll to 0.2° accuracy.

SMALL FORM FACTOR

Smallest Imaging Sonar available.

> BROADBAND TRANSDUCER

Excellent image quality & range.

NO SLIP RINGS

No components to wear.



Impact Subsea are proud to present the world's most compact imaging sonar - the ISS360.


Optionally available with integrated Pitch & Roll.

Utilising a broadband composite transducer together with an advanced digital acoustic engine provides excellent range capability and image clarity.

For applications where Sonar Imaging, Pitch & Roll are required; all can be provided from a single device.

The use of Compressed High Intensity Radar Pulse (CHIRP) acoustic signalling enables a significant increase in range resolution while maintaining an excellent range capability.

Provided in a highly robust Titanium housing. The unit can be supplied without pitch and roll. Alternative configurations are available upon request.



*Optional





ISS360

HIGH PERFORMANCE IMAGING SONAR



ACOUSTIC

Frequency 700kHz Centre

600 to 900kHz Bandwidth

Range 0.15 to 90 meters (4,000m rated)

0.15 to 80 meters (6,000m rated)

Resolution 2.5mm (minimum)

Beam Angle 23° Vertical at 700kHz

2.2° Horizontal at 700kHz

Signalling CHIRP & CW

Selectable

0.225°, 0.45°, 0.9°, 1.8°, 3.6° & 7.2° Step Size

Selectable

Scan Angle 360° Continuous or Sector Scan

PHYSICAL

Depth Rating 4,000m & 6,000m

Temperature -10 to 40°C Operating

-20 to 60°C Storage

Connector Subconn MCBH8M-SS

Other options available

Weight 0.38/0.3kg (4,000m)

Air/Fresh water 0.37/0.3kg (6,000m)

ATTITUDE*

Pitch ± 90°

± 180° Roll

0.2° Accuracy

Resolution 0.1°

COMMS & POWER

Digital RS232, RS485 & Ethernet

Protocol 9600 to 115,200 baud


12 to 65V DC Input Voltage


Power 95mA @ 24V DC

Standby

Power 240mA @ 24V DC

Scanning¹





Dimensions given in mm.

*Optional

¹ Based on maximum power level and scanning speed.

